

**Hosefloats**, an industry standard for the floatation of hoses, conduit and cables for dredging, mining and marine applications.

An easy to install solution that allows pipes to bend and flex, while maintaining low resistance to waves, wind and current.

## Inclusions

### A hosefloat set comprises:

- 2 pipefloat halves
- 2 variable rubber bushes
- A galvanised assembly kit which includes:
  - 4 bolts
  - 4 nuts
  - 8 washers

## Specifications

- Manufactured from polyethylene.
- Standard colour is yellow or red.
- Stainless steel inserts used in crush areas.
- Rubber Bushes are manufactured from EDPM which is totally resistant to harsh environments.
- All floats are pressure tested prior to despatch.
- Recyclable and VOC Free.
- Australian made and designed.
- Specifications are subject to change without notice.

## Stainless Steel Kit

Marine Grade, SAE 316 stainless steel assembly kits for corrosive environments are available at an additional cost.

- Kit includes: 4 Rods, 8 Nuts and 8 Washers.

## Hosefloat 160

### FLOAT O/D 460mm

HOSE O/D	LENGTH	WEIGHT	RESERVE BUOYANCY
10 - 50 mm	900 mm	12.0 kg	132 kg
50 - 80 mm	900 mm	12.0 kg	132 kg
80 - 130 mm	900 mm	12.0 kg	132 kg
130 - 160 mm	900 mm	12.0 kg	132 kg

**2 x RUBBER BUSH PER FLOAT** 2.0 kg

### HOSEFLOAT SPACING GUIDE


**Water** : 4 sets for every 12 meters of pipe  
**Slurry** : 7 sets for every 12 meters of pipe  
eg. 100m Waterpipe: (100m/12m) x 4 = **33 Floats**

### PACKING GUIDE

### PALLET LOAD

1.2m x 1.35m x 2m (height)  
12 Sets per pallet  
Approx 175 kg + Pallet

\* **RESERVE BUOYANCY** is the weight the float will carry before full submergence.  
\* **O/D** is the Outside Diameter.  
\* Dimensions and weights are nominal.



Variable Rubber Bush to suit hose, conduit or cable diameters from 10mm to 130mm.