



Pipefloats, an industry standard for the floatation of pipes, hoses and cables for dredging, mining and marine applications.

An easy to install solution that allows pipes to bend and flex, while maintaining low resistance to waves, wind and current.

Inclusions

A pipefloat set comprises:

- 2 pipefloat halves
- A galvanised assembly kit which includes:
 - 4 bolts
 - 4 nuts
 - 8 washers

Specifications

- Manufactured from polyethylene.
- Manufactured in safety orange.
- Stainless steel inserts used in crush areas.
- All floats are pressure tested prior to despatch.
- Recyclable and VOC Free.
- Australian made and designed.
- Specifications are subject to change without notice.

Stainless Steel Kits

Marine Grade, SAE 316 stainless steel assembly kits for corrosive environments are available at an additional cost.

- Kit includes: 4 Rods, 8 Nuts and 8 Washers.

Small Series Pipefloats

FLOAT O/D 460mm

PIPE O / D	LENGTH	WEIGHT	RESERVE BUOYANCY
160 mm	900 mm	12.0 kg	132 kg
200 mm	900 mm	12.0 kg	106 kg
225 mm	900 mm	12.0 kg	80 kg

PIPEFLOAT SPACING GUIDE

Water : 4 sets for every 12 meters of pipe
Slurry : 7 sets for every 12 meters of pipe
 eg. 100m Waterpipe: (100m/12m) x 4 = **33 Floats**

PACKING GUIDE

PALLET LOAD

1.2m x 1.35m x 2m (height)
 12 Sets per pallet
 Approx 155 kg + Pallet

* **RESERVE BUOYANCY** is the weight the float will carry before full submergence.
 * **O/D** is the Outside Diameter.
 * Dimensions and weights are nominal.

